



piSmart-Gateway-LR

Article number: 911131090



Unique Features

- LoRaWAN
- Nahbereichsfunk
- Matter/ Thread/Zigbee
- GNSS
- microSD-Karte
- Beschleunigungssensor
- Low Power
- Optional: induktives Laden

Description

The piSmart-Gateway-LR is an energy-efficient LoRaWAN IoT gateway. It is used as a GPS tracker, data logger, for data acquisition, or as a retrofit module in devices, machinery, vehicles, or industrial plants.

- › LoRaWAN for energy-efficient data transmission over long distances
- › GPS for precise device location
- › µSD card slot for recording various data such as position or self-acceleration
- › Various inputs and outputs for flexible adaptation to the application
- › Periodic system waking for long runtime
- › Cloud platform pironex-iot.de for data visualization and analysis

Place of use

- › Outdoor
- › Indoor
- › rough Environment (IP67)

Operating Location

As a module with low energy consumption, it is ideally suited for applications that require minimal maintenance. The piSmart-Gateway-LR specifically covers remote tasks:

- › Remote control of industrial plants, for example
- › Control of sensors, actuators, or other devices in home automation
- › GPS tracking
- › Asset tracking
- › Sensor data acquisition
- › Geofencing
- › Theft protection and access systems

The gateway is designed specifically for extreme environments with limited space and withstands water, shocks, vibrations, and extreme temperature conditions.

Application-specific modifications are possible – allowing customization of the form factor, interfaces, and performance according to customer needs.

Audience / users

- › B2B,
- › Hard- and Software developer



piSmart-Gateway-LR

Article number: 911131090

Technical data

Microcontroller/Processor

Processor 1	STM32WLE5JC 32-bit Arm® Cortex®-M4 CPU up to 48 MHz
SRAM	65KB
Flash	up to 256KB
Processor 2	EFR32MG24 32-bit ARM® Cortex®-M33 up to 72 MHz
RAM	256kB
Flash	1536KB

Interfaces

Qi Charging Interface	inductive charging up to 1,25A
LoRaWAN	Antenna on Board, optional: U.FI-Connector for external antenna
Frequency/Band	868MHz
Transmission Power	22dBm
GNSS	optional: U.FI-Connector for external antenna
Frequency/Band	GPS: 1575MHz GLONASS: 1597.5MHz BeiDou: 1561MHz
Transmission Power	15dBm
Matter/Thread/Zigbee	IEEE 802.15.4, uses same antenna as Bluetooth
Frequency/Band	2.4GHz
Transmission Power	up to 20dBm
Programming Interface	SWD (internal)
Power Supply (opt.)	12V via Terminalblock



piSmart-Gateway-LR

Article number: 911131090

Additional Features

Card Slots	1x microSD/microSDHC
Sensors	3G Sensor: · 3 Axis · up to 12bit resolution · $\pm 2\text{ g}$ / $\pm 4\text{ g}$ / $\pm 8\text{ g}$ / $\pm 16\text{ g}$ · 1Hz to 5,3kHz
Piezo Driver	for piezo speaker, up to 18Vpp, 20Hz to 300kHz
Real Time Clock	32.768kHz crystal, Alarm function, Countdown-Timer
Optical Elements	1x green LED (Status)
Control Elements	1x Switch (Wakeup)

Environmental Conditions

Operating Location	Indoor, Outdoor: only within the limits mentioned below
Operating Temperature	-20 °C to +60 °C
Temperature while charging	+10 °C to +45 °C
Storage Temperature	-20 °C to +60 °C
Transport Temperature	-20 °C to +60 °C
Gradient of Temperature	5 K/min (avoid dew)
Relative Humidity	Max. 70%, avoid dew
Height above Sea Level	up to 2000 m
Height above Sea Level (Storage/Transport)	up to 3000 m
Degree of Pollution	Pollution Degree 2

Voltage Supply

Voltage VDC	5V-20V at receiver coil or 12VDC
max. Power Pmax	5W
max. Current Imax	420mA @ 12VDC
Battery	1x Lithium-Polymer battery or up to 2 primary cells, variable charge
Withstand Voltage	26.4V @12VDC Input
VB(t) - Turn-Off Threshold	3.2VDC (battery voltage)
VB(t) - Turn-On Threshold	3.2VDC (battery voltage)
VB(t) - Undervoltage Lookout	<3.4 VDC (battery voltage)
VB(t) - Overvoltage Lookout	> 4.2 V (battery voltage)
Reverse Polarity Protection	yes



piSmart-Gateway-LR

Article number: 911131090

Directives

2014/53/EU	Radio Equipment Directive
2011/65/EU	Restriction of certain Hazardous Substances (ROHS)
2012/19/EU	Waste of Electrical and Eletronic Equipment (WEEE)
EC 1907/2006	Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

Mechanic Specifications

Dimensions	88,2 mm x 111 mm x 30 mm
Weight	<300 g
IP-Class	IP67 (DIN EN 60529:2014-09; VDE 0470-1:2014-09)
Material	ABS and PA6
Resistance of the Housing against UV-Light	ja
Mounting Type	screws

Technical drawing (dimensions in mm)

